

ViewSonic®

## A72f Ultimate Desktop™ Display



### A - Series

#### 17" (16.0" viewable) Ultimate Desktop Display

The days of boring, putty-colored monitors are over! ViewSonic® announces the A72f 17" (16.0" viewable) monitor in a stylish metallic hue. Combine this CRT with our matching wireless keyboard and mouse (sold separately) for the Ultimate Desktop™ solution. Style aside, this monitor has a PerfectFlat® screen for edge-to-edge distortion-free viewing. All this style and technology make the A72f perfect for detailed business applications and Internet use. Stop by your local retailer today and see the latest marriage of style and technology, only from ViewSonic.

- **Ultimate Desktop metallic hue**

Give your desktop a makeover. Add the matching wireless keyboard and mouse (sold separately) for a complete package.

- **PerfectFlat® screen**

PerfectFlat screen delivers bright colors, straighter lines, and virtually no glare.

- **Matching wireless keyboard and mouse**

Offers radio frequency technology which is more advanced than infrared technology. Keyboard and mouse utilize PS/2 port freeing up USB connectors.

- **0.20mm horizontal dot pitch**

This super fine dot pitch produces clear, crisp images with great picture definition, even at the highest resolutions.

- **1280 x 1024 maximum resolution**

Displays a maximum resolution of 1280 x 1024; 1024 x 768 at an 87Hz flicker-free refresh rate for easy viewing.

1280 x 1024 @ 66Hz

1024 x 768 @ 87Hz

800 x 600 @ 110Hz

640 x 480 @ 135Hz

- **E-Color's True Internet Color® and Colorific®**

Color management software included for reliable colors when users visit E-Color Corrected™ web sites. Colorific® ensures precise color matching from screen to other color peripherals.

- **Three-year limited warranty**



**ViewSonic®**  
*See the difference.®*



# ViewSonic A72f Ultimate Desktop™

A  
SERIES

Ultimate Desktop™ Wireless Keyboard and Mouse sold separately

17" (16.0" VIEWABLE) COLOR MONITOR WITH SUPER FINE DOT PITCH FOR SUPERIOR IMAGES

CRT	Type	17" (16.0" diagonal viewable area) PerfectFlat® 0.20mm horizontal / 0.25mm diagonal dot pitch, 90° deflection
	Phosphor Glass Surface	RGB medium-short persistence Tint (TM=52.6%) anti-static, anti-glare screen treatment
INPUT SIGNAL	Video	RGB analog (0.7Vp-p, 75 ohms)
	Sync	H/V Separate (TTL), composite sync
	Frequency	F <sub>H</sub> :30-70kHz, F <sub>V</sub> :50-180Hz
COMPATIBILITY	PC	IBM® XT, AT, 386, 486, Pentium®, PS/2 and compatibles (from VGA up to 1,280 x 1,024 non-interlaced)
	Mac®*	Power Mac™ (up to 1152 x 870)
CONNECTOR	Signal	15-pin mini D-sub, attached cable
	Power	3-pin plug (IEC320)
POWER	Voltage	AC 90-132V/180-264VAC (auto switch) 50/60 (+/-3)Hz
	Consumption	85W (typ)
USER CONTROLS	Basic	Power on/off, Key-1, Key-2, down, up
	OnView®	Contrast, brightness, H/V-position, H/V-size, pincushion, pin-balance, degauss, trapezoid, rotation, ViewMatch® color, parallelogram, tilt, corner hooking, ViewMeter®, language select, recall
VIDEO INPUT	Bandwidth	108MHz (typ)
MISCONVERGENCE		0.3mm (max) at center
		0.4mm (max) at corner
DISPLAY AREA	Factory Setting	310mm(H) x 232mm(V) (Dependent upon
	Maximum Scan	325mm(H) x 244mm(V) signal timing used)
OPERATING CONDITION	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	5% to 95% (non condensing)
DIMENSIONS	Physical	408mm (W) x 428mm (H) x 420mm (D) (16.1" x 16.8" x 16.5")
WEIGHT	Net	16.5Kg (36.4 lbs.)
OTHER		DDC1 & DDC2B, GTF
REGULATIONS		UL, cUL, FCC-B, DHHS, MPR-II, DOC-B, CB, CE, EPA, Energy 2000
POWER MANAGEMENT		Meets ENERGY STAR®, VESA® DPMS standards
WARRANTY		Three-year limited warranty on CRT, parts and labor. 48-hour Express Exchange® Service option available**

## • OnView® controls including ViewMatch®

All screen adjustments are made via an on-screen menu using simple controls. ViewMatch allows the user to adjust color temperature and individual color intensity for screen-to-print matching.

## • Anti-static, anti-glare screen

This screen treatment refracts unwanted light away from the user while maintaining the highest image quality.

## • MPR-II and ENERGY STAR® compliant

This monitor complies with the world's strictest standards for low radiation, safety, ergonomics, recycling and power conservation while saving cost through automatic power saving modes.

## • Plug & Play†

Fully supports the Microsoft® Windows® auto-installation standard for easy, trouble-free configuration and setup.

## • PC and Mac® compatible

## • PC '99 compliant

Compliant with Microsoft® hardware guidelines for increased ease of set up and installation.

## • Base accommodates optional ViewSonic USB Hub



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 and ISO 14001 by the British Standards Institution



**ViewSonic®**  
See the difference.®

381 Brea Canyon Road, Walnut, CA 91789 • Phone (800) 888-8583 • (909) 869-7976 • Fax (909) 869-7958 • Internet: [www.ViewSonic.com](http://www.ViewSonic.com)

\*Free universal Mac® cable adapter available. \*\* Only available within the United States. Copyright © 2001 ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. The EPA only promotes energy efficiency and does not endorse any particular company or product. VSA72f\_3/01\_web [10015-01E 04/01]